



## Metall detector, General purpose

**Art.-No.: 170282**

## Metal detector, high sensitivity

**Art. - No.: 170293**



A metal detector for personnel search with an instant audible and visual alarm. Automatically adjusts for optimum performance to any target and is effective on all metals, including ferrous, non-ferrous and stainless steel, objects down to 0,1 g

Low power consumption gives 12 months operation (daily use) on a single battery. High impact resistant black ABS case. Supplied with wrist strap and batteries.

### Specification:

Sensitivity	Target size down to 0,10 grams
Weight	262 g
Dimensions	365 mm x 55 mm x 30 mm
Operation	Single push button
Response	Instantly
Alarm	No metal present = no alarm Clear audible alarm (digital go-no go) combined with visual LED
Battery	Battery inserted "cartridge style" - All equipment supplied complete with 9 V Battery (NiCad-optional)
Electronics	Ultra high reliable hermetically sealed
Operating temperature	-20° , +65° C
Case	Rugged construction-high impact resistant ABS moulded case, (IP64)
Battery indicator	Audio/LED

Fully automatic self adjusting circuits

**Modell: AD 10-2**

A more sensitive detector effective on metal objects down to 0.05g (ferrous, non-ferrous and stainless steel). Automatically adjusts for optimum performance to any target and signals with an audible/visual alarm or for more discreet detection a visual alarm only.

Low power consumption gives 12 months operation (daily use) on a single battery. High impact resistant black ABS case. Supplied with wrist strap and batteries.

### Specification:

Sensitivity	Target size down to 0,05 grams
Weight	262 g
Dimensions	365 mm x 55 mm x 30 mm
Operation	Auto-ranging-automatically adjusts for optimum performance
Response	Instant response to all metals, including stainless steel
Alarm	No metal present = no alarm Switchable audible alarm on/off with visual LED enabling silent use if required
Case	Rugged construction-high impact resistant ABS moulded case, (IP64)
Battery	Battery inserted "cartridge style" - All equipment supplied complete with 9 V Battery (NiCad-optional), up to 12 month daily use from one battery
Electronics	Ultra high reliable hermetically sealed

Fully automatic self adjusting circuits

**Model: AD 11-2**

Medically tested and approved no risks for persons with pacemakers

Specifications are subject to change without notice!